

MEASUREMENT OF THE EXPOSURE OF HUMAN POPULATIONS TO ENVIRONMENTAL RADIATION

By WAYNE M. LOWDER and WILLIAM J. CONDON
Health and Safety Laboratory,
U.S. Atomic Energy Commission, New York

THE accurate determination of representative exposure-levels of large human populations to ionizing radiation in the environment has proved to be a problem of considerable interest to the biologist and of comparable difficulty for the physicist. In an attempt to evaluate existing techniques for obtaining such information, the Health and Safety Laboratory and the Harvard School of Public Health in 1962 undertook concurrent investigations of population exposure to environmental radiation in selected areas of the States of Vermont and New Hampshire using two independent methods. These investigations have been discussed by Segall¹ and by Lowder *et al.*², and the extensive results are presented in detail in more recent reports^{3,4}. In this article, we directly compare the two sets of population exposure measurements, discuss briefly some of the alternative methods available for such surveys, and present some general conclusions relating to the state of the art which can be derived from our experience in the New England work. The results given here, which partially supersede the preliminary results reported previously^{1,2}, provide a useful background for considering the general problems associated with making such measurements and interpreting them properly.

The areas chosen for investigation (see refs. 1-4) contain a considerable proportion of the population of the two states, including the major urban centres. Interest in these areas was stimulated initially by the fact that the various underlying bedrock formations appear to differ widely in mean content of naturally occurring radio-nuclides, as estimated by either direct field and laboratory sample radiometry or inferences from information on similar formations elsewhere⁵. It seemed possible that these differences in mean bedrock radioactivity might be reflected in significant differences in mean radiation exposure between the populations of these areas.

Entirely unrelated approaches were utilized by the Health and Safety Laboratory and Harvard groups in

attempting to obtain realistic estimates of population exposure to environmental radiation. The Health and Safety Laboratory team conducted *in situ* measurements of the radiation field, both out of doors and within residences, to provide a general radiation profile over the populated area, and weighted these results by estimates of mean occupancy time in the various types of locations. This method was first utilized on a large scale by Spiers *et al.* in Great Britain^{6,7}, and another investigation of this type was carried out in Switzerland in 1961 (ref. 8). The Harvard group undertook a more direct approach and distributed integrating dosimeters to representative members of the population to be worn on the person.

For the purpose of comparing the two sets of results, we have defined 'population exposure' as the free air dose 'experienced' by typical individuals in their usual rounds of activity. We consider only the air dose from the more penetrating components of the environmental radiation field, that is, the terrestrial γ - and ionizing cosmic radiation. This definition can be justified by the fact that the mean γ -doses to the skin and at various depths in the body are fairly well-known fractions of the free air γ -dose^{9,10}, and only the more penetrating components of the external radiation field significantly contribute to the dose at the depths of greatest interest, that is, those of the gonads and bone. It should be noted that the possibly important tissue dose contribution from cosmic ray neutrons is not determined by the techniques used in these investigations.

The Health and Safety Laboratory radiation survey was carried out in July and August 1962, and subsequent check measurements were made in May and September 1963 and May 1964. The instrumentation included high-pressure argon ionization chambers for total dose-rate measurements, a γ -spectrometer system for determination of component dose rates (particularly necessary for discrimination between the natural and fall-out γ -radiation), and portable scintillation detectors for surveys of the areas surrounding each outdoor measurement location as well as for the indoor measurements. The survey techniques, described in detail elsewhere¹¹⁻¹³, provide an overall accuracy of ± 5 per cent (*S.D.*) for the measured total dose-rate values and approximately ± 10 per cent for each of the various components of the total radiation field. The outdoor readings were taken in large, flat open spaces situated in populated areas (for example, parks, fields, lawns, vacant lots) with the instruments placed 3 ft. above the ground. The number of measurements in each area was determined by its population and size, the availability of proper sites, and the observed range and pattern of the previous readings. A sufficient number was taken to ensure that a reasonable radiation profile could be constructed for each area. The quite limited

obtain realistic estimates of population environmental radiation. The Health and Safety Commission conducted *in situ* measurements in the field, both out of doors and within buildings, and weighted these results by estimates of the time spent in the various types of locations. This was first utilized on a large scale by Spiers and others in Britain^{6,7}, and another investigation of this type was carried out in Switzerland in 1961 (ref. 8). The Commission undertook a more direct approach and used portable dosimeters to represent the population to be worn on the person. The value of comparing the two sets of results, 'population exposure' as the free air dose rate for typical individuals in their usual rounds, and 'personal exposure' as the air dose rate from the components of the environmental radiation from terrestrial γ - and ionizing cosmic radiation, can be justified by the fact that the dose to the skin and at various depths in the body from the well-known fractions of the free air dose rate by the more penetrating components of the radiation field significantly contribute to the total dose of greatest interest, that is, those of the body. It should be noted that the possibly largest dose contribution from cosmic ray dose rate is determined by the techniques used in the survey.

The Health and Safety Laboratory radiation survey was carried out in July and August 1962, and subsequent surveys were made in May and September 1963. The instrumentation included high-purity ionization chambers for total dose-rate measurements, a spectrometer system for determination of dose rates (particularly necessary for distinguishing between the natural and fall-out γ -radiation), and scintillation detectors for surveys of the radiation field at outdoor measurement locations as well as for indoor measurements. The survey techniques are detailed elsewhere¹¹⁻¹³, provide an overall accuracy of ± 10 per cent for the measured total dose rate. Components of the total radiation dose rate were taken in large, flat open areas (for example, parks, sports grounds) with the instruments placed at various distances from the area. The number of measurements in each area was determined by its population and size, the background radiation, and the observed range and variability of readings. A sufficient number of measurements at a reasonable radiation profile was taken for each area. The quite limited

range in the measured dose rates in each case (± 10 per cent about the mean for most field readings) meant that relatively few locations were required for this purpose. Most of the measurements were made in the larger towns, as these contained the bulk of the population.

The mean γ -dose rates over open ground derived from the spectrometer readings are given in Table 1 for each of the eight regions chosen for examination. The main towns and the corresponding bedrock formations are indicated. The spectrometric procedures allow determinations of the component dose rates from potassium-40, the uranium and thorium series, and the main fall-out γ -emitters (⁹⁵Zr-⁹⁵Nb, ¹⁰³Ru, ¹⁰⁶Rh, ¹³⁷Cs). Estimates of mean soil concentrations of the natural radioisotopes can be calculated from the component dose rates, assuming uniform depth distribution in the ground^{10,11}. Such concentration values are representative of the true soil contents of radium, uranium and thorium only when these isotopes are in radioactive equilibrium with their γ -emitting daughters. These results are included in Table 1, and the mean values for the natural emitters are combined to give a mean 'equivalent uranium' (eU) concentration for the upper layers of the ground, that is, the amount of uranium in equilibrium with its daughters that would yield the same γ -dose rate as the potassium and the uranium and thorium series in the actual situation. Also listed for comparison purposes are the mean equivalent uranium contents of the various bedrocks as estimated by Billings⁵. It is noteworthy that the range of soil activities is much narrower than that inferred for the bedrock formations.

The average fall-out levels indicated in Table 1 apply specifically to July and August 1962, when almost all readings fell between 2 and 3 μ r./h. When some of these sites were re-checked in 1963, the fall-out dose rates were nearly twice as great, ranging from 3 to 5 μ r./h. In all cases, ⁹⁵Zr-⁹⁵Nb was the dominant contributor. By May 1964, levels of 1 μ r./h were typical, the ⁹⁵Zr-⁹⁵Nb and other short-lived emitters having nearly disappeared, leaving ¹³⁷Cs as the most important fall-out γ -emitter. These results are quite consistent with the more detailed information available for the New York City area during this period¹⁴.

In addition to the combined ionization chamber and spectrometer readings summarized in Table 1 (5-10 in each region, except for 16 at Conway), separate ionization-chamber readings were made at many other sites along with a number of independent portable scintillometer surveys. The uniformity of the outdoor radiation levels in each area was remarkable. In general, streets and sidewalks did not significantly alter the observed profile.

Any attempt to estimate population exposure to environmental radiation must take into account the

3.14 8.74
 5.2 10.9

 11.2 78.84
 438 81.2

 455 64

Table 1. MEAN OUTDOOR γ -RADIATION LEVELS

Region	Bedrock	eU* (p.p.m.)	K		U		Th		Natural γ eU		Fall-out γ μ r./h
			μ r./h	%	μ r./h	p.p.m.	μ r./h	p.p.m.	μ r./h	(p.p.m.)	
New Hampshire											
1. Manchester	Fitchburg Granite	23	2.5	1.5	1.1	1.5	3.4	9.4	7.0	9.2	2.2
2. Concord	Binary Granite	26	2.9	1.7	1.2	1.6	4.3	11.9	8.4	11.1	2.2
3. Franklin	Littleton Formation	23	2.4	1.4	1.2	1.6	3.5	9.7	7.1	9.4	1.8
4. Conway	Conway Granite	45	3.6	2.1	1.7	2.2	5.6	15.6	10.9	14.3	2.7
Vermont											
1. Rutland	Dunham Dolomite	5	2.6	1.5	1.0	1.3	2.0	5.6	5.6	7.4	2.3
2. Middlebury	Beldens Formation	5	3.2	1.9	0.8	1.1	2.6	7.2	6.6	8.7	2.0
3. Bennington	Glacial Drift	9	3.3	1.9	1.0	1.3	2.2	6.1	6.5	8.6	2.0
4. Burlington	Monkton Formation	11	2.4	1.4	1.0	1.3	1.8	5.0	5.2	6.8	2.4

* Mean bedrock radioactivity as estimated by Billings*.

Table 2. MEAN WEEKLY DOSES IN MR./WEEK

Geological category	eU (p.p.m.)	Outdoor Natural γ	Outdoor Total γ *	Cosmic	Mean population exposure		
					1962†	Natural	Dosimeters
Dunham Dolomite	5	0.94	1.34	0.62	1.69	1.37	2.97
Beldens Formation	5	1.11	1.43	0.60	1.74	1.49	2.86
Glacial Drift	9	1.09	1.43	0.62	1.76	1.49	3.01
Monkton Formation	11	0.87	1.27	0.59	1.61	1.29	2.70
Fitchburg Granite	23	1.18	1.52	0.60	1.82	1.54	3.13
Littleton Formation	23	1.19	1.63	0.61	1.91	1.56	2.97
Binary Granite	26	1.41	1.78	0.60	2.05	1.73	3.21
Conway Granite	45	1.83	2.27	0.61	2.43	2.07	3.67

* Includes fall-out, averaged over all locations within an area.

† Obtained as indicated in the text; in units of air dose rate.

mean bedrock radioactivity as estimated by Billings⁴.

Table 2. MEAN WEEKLY DOSES IN MR./WEEK

Geological category	eU (p.p.m.)	Outdoor Natural γ	Outdoor Total γ *	Cosmic	Mean population exposure		
					1962†	Natural	Dosimeters
Dunham Dolomite	5	0.94	1.34	0.62	1.69	1.37	2.97
Beldens Formation	9	1.11	1.43	0.60	1.74	1.49	2.86
Glacial Drift	11	1.00	1.43	0.62	1.76	1.49	3.01
Monkton Formation	23	0.87	1.27	0.59	1.61	1.29	2.70
Fitchburg Formation	23	1.18	1.52	0.60	1.82	1.54	3.13
Littleton Formation	26	1.19	1.63	0.81	1.91	1.56	2.97
Binary Granite	45	1.41	1.78	0.60	2.05	1.73	3.21
Conway Granite	45	1.88	2.27	0.61	2.43	2.07	3.67

* Includes fall-out, averaged over all locations within an area.
 † Obtained as indicated in the text; in units of air dose rate.

effect of man-made structures on ambient radiation fields, since most individuals spend a large fraction of their time indoors. Portable scintillation detector readings were made in 160 private homes and apartments in the main towns to ascertain whether any consistent relationship existed between indoor and outdoor radiation-levels. Several rooms in each dwelling were surveyed, including the living-room and at least one bedroom. Again, a strong uniformity exhibited itself in that the mean indoor levels were close to 70 per cent of the corresponding outdoor levels in each area⁴. This may be related to the fact that the vast majority of the dwellings were of wood-frame construction, with the building materials appearing to act generally as γ -ray shields with relatively little activity of their own.

With such data at hand, an estimate of mean population exposure to environmental radiation can be obtained by calculating a suitably weighted average of the indoor and outdoor readings of the survey instruments. Taking into consideration the greater occupancy time indoors of the average individual, the mean exposure levels have been estimated to be 80 per cent of the mean outdoor terrestrial γ -dose rates given in Table 1, plus the contribution from the ionizing components of the cosmic radiation at the ground altitudes of the various areas¹⁵. No correction of the cosmic-ray figures for typical structural shielding has been made, since this would be a reduction of the order of 10 per cent or less, which is comparable to the present uncertainty in the absolute cosmic-ray ionization intensity.

Table 2 shows the population exposure data arranged by geological region. The mean weekly outdoor doses in air are given for both natural and total (natural plus fall-out) γ -radiation and for cosmic rays, and the Health and Safety Laboratory population exposure estimates for the time of the survey (August 1962, including fall-out) and for the natural emitters only (that is, the mean life-time levels neglecting fall-out) are also given. The importance of the spectrometric technique is emphasized by the fact that estimates of the integrated natural γ -dose were obtainable even under conditions of near-maximum fall-out contamination. In many population investigations, it is just this quantity that is desired.

The Harvard investigation involved the use of a set of 200 Victoreen model 362 condenser ionization-chamber pencils, along with a stable pulse height readout system^{16,17} which is designed to allow readings of 1.0 ± 0.2 mr. at the 95 per cent confidence level with a single pencil. Mechanical and thermal stability was tested, and corrections made for average leakage rates observed in the laboratory.

These dosimeters were distributed in pairs to five individuals in standard occupational categories in each of 16 areal units, half urban and half rural. The dosimeters

were worn for one week, collected, read, and then redistributed. The experiment was conducted for five weeks, resulting in a total sampling of 400 individuals, 25 in each areal unit (that is, 50 in each of the eight geological regions). The details of this study are discussed by Segall^{1,3}.

Estimates of population exposure from the mean values of the Harvard dosimeter data in the various areas are given in the last column of Table 2. These air dose values are derived from Segall's data^{1,3} by assuming that each of the dosimeters, worn on the body surface, read 100 per cent of the cosmic-ray ionization and 85 per cent of the γ -ray ionization in free air. The latter figure is based primarily on the recent measurements of body attenuation factors by Spiers and Overton⁶.

The Health and Safety Laboratory and Harvard population exposure results are plotted as a function of estimated mean bedrock radioactivity in Fig. 1, with the respective regression lines indicated. Plotted also in Fig. 1





Fig. 1. Environmental radiation in the eight selected areas of northern New England as a function of estimated mean bedrock radioactivity. A, Population exposure estimates from Harvard dosimeters; B, population exposure estimates based on Health and Safety Laboratory *in situ* measurements; C, mean weekly outdoor γ doses

one week, collected, read, and then re-experiment was conducted for five weeks, al sampling of 400 individuals, 25 in each is, 50 in each of the eight geological details of this study are discussed by

population exposure from the mean values dosimeter data in the various areas are column of Table 2. These air dose values Segall's data^{1,3} by assuming that each of on the body surface, read 100 per ray ionization and 85 per cent of the n free air. The latter figure is based cent measurements of body attenuation and Overton⁹. and Safety Laboratory and Harvard e results are plotted as a function of rock radioactivity in Fig. 1, with the lines indicated. Plotted also in Fig. 1



on in the eight selected areas of northern estimated mean bedrock radioactivity. es from Harvard dosimeters; B, popu on Health and Safety Laboratory *in situ* mean weekly outdoor γ doses

(lowest curve) are the mean outdoor natural γ -levels obtained from the Health and Safety Laboratory spectrometer readings. These values are directly proportional to mean soil content of natural radioactivity (1 mr./week \rightarrow 7.83 p.p.m. eU).

It is readily apparent from the figure that the two sets of population exposure data show a considerable systematic difference. The large intercept at zero bedrock radioactivity for the linear fit to the Harvard dosimeter data cannot be explained simply on the basis of the relatively constant cosmic-ray and fall-out dose contributions, which are less than 1.0 mr./week. There is certainly no evidence to suggest that building materials produce elevated radiation levels indoors in any consistent manner. The intercept for the Health and Safety Laboratory results is more reasonable, although also somewhat high. It is interesting to note that, while an apparent linear trend appears to exist for all sets of data, the interpretation of this trend is not obvious. For example, the slope of the natural γ -dose regression line is only one-sixth of that expected if the bedrock were the source of the radiation¹¹. In a sense, the results shown in Fig. 1 provide a rough indication of the influence of bedrock geology on soil radioactivity and natural radiation exposure in these areas. The effect is small and may be of practical significance only in the Conway area, where the reddish sand derived from the thorium-rich Conway granite is present in the soil throughout the populated areas. The trend of the results in Fig. 1 may be indicative of some fairly consistent relation in these areas between the bedrock formations and their respective overburdens of soil in terms of natural radioactivity. The apparent near-linearity of the population exposure estimates as a function of bedrock radioactivity derives from the similar relationship between estimated mean soil and bedrock radioactivities, since the outdoor (and to some extent the indoor) radiation-levels to which the general population is exposed are closely related to the content of natural γ -emitting radioisotopes in the upper layers of the soil.

Fig. 2 shows the Harvard dosimeter data plotted directly as a function of the Health and Safety Laboratory 1962 total exposure results. The high degree of correlation ($r > 0.9$) between the Harvard and Health and Safety Laboratory estimates of population exposure is evident; a line of unit slope fits the data quite well. The 1.2 mr./week value for the Y-axis intercept of this line is a measure of the apparently systematic deviation between these two sets of data. While not enough information is at present available to explore this problem fully, one obvious possibility is that the pocket dosimeters consistently exhibited enhanced leakage under field conditions as compared with that measured in the laboratory and corrected for in the data interpretation.





Fig. 2. Harvard population exposure estimates as a function of comparable Health and Safety Laboratory (HASL) estimates for the eight New England areas examined

In any event, there is little doubt that the dosimeter results are too high. This can be shown by carrying out a simple mathematical analysis of the various contributions to the population exposure-level, P , utilizing the accurate Health and Safety Laboratory measurements of outdoor environmental radiation dose rates. If I_c , I_n and I_f are the measured mean outdoor dose-rate contributions from cosmic, natural γ -, and fall-out γ -radiation, respectively, and I_h is the mean indoor γ -dose rate produced by sources in the building materials, we can write the following expression for P :

$$P = f_i (I_c + s_f I_f + s_n I_n + I_h) + f_o (I_c + I_f + I_n)$$

where f_i and f_o are occupancy time factors for indoor and outdoor locations, respectively, and s_f and s_n are mean transmission factors of the buildings and residences for outdoor fall-out and natural γ -radiation. Substituting



Population exposure estimates as a function of community Laboratory (HASL) estimates for the eight England areas examined

It is little doubt that the dosimeter data can be shown by carrying out a detailed analysis of the various contributions to the exposure-level, P , utilizing the accurate laboratory measurements of outdoor and indoor dose rates. If I_c , I_n and I_f are the indoor dose-rate contributions from indoor sources, and I_o is the outdoor dose-rate contributed by sources outdoors, we can write the following

$$P = s_n I_n + I_o + f_o (I_c + I_f + I_n)$$

where s_n and f_o are correction factors for indoor and outdoor dose rates, respectively, and s_f and s_n are mean correction factors for the buildings and residences for outdoor γ -radiation. Substituting

reasonable values for these factors and the various weekly doses into the formula, we get:

$$P = 0.8 [0.60 + (0.2)(0.37) + (0.3)(1.18) + I_h] + 0.2 [0.60 + 0.37 + 1.18] = 1.25 + 0.8 I_h \text{ mr./week}$$

Since we have determined that the indoor total γ -levels average 0.7 of the outdoor levels in these areas, we find that:

$$I_h = 0.5 I_f + 0.4 I_n = 0.66 \text{ mr./week}$$

Substituting this in the above expression for P , we get:

$$P = 1.8 \text{ mr./week}$$

This result is not strongly dependent on the particular values assumed for the various factors in the above equation. It is quite consistent with the similarly calculated Health and Safety Laboratory population exposure estimates, and much lower than the dosimeter results. The mean contribution from building materials to population exposure would have to be close to 2 mr./week to validate the dosimeter data, which is considerably higher than the measured values for the total indoor γ -dose rate in most of the 160 residences where scintillation detector readings were made. Even without such evidence, it seems to be an unreasonably high value to assign to mean regional indoor radiation-levels produced by radioactivity in building materials. For it implies total indoor γ -doses averaging approximately 3 mr./week, whereas the scattered data given in the 1962 United Nations report¹⁸ indicate that readings of 1 mr./week are typical of normal situations in wood or brick houses.

The results of both surveys indicate that the range of population exposure to environmental radiation is quite narrow throughout the regions studied. It follows that northern New England does not provide a good 'laboratory' for the study of the effect on large human populations of differences in long-term environmental radiation exposure. Of much greater significance is the correlation between the two entirely independent and undoubtedly somewhat imprecise techniques for estimating these exposure-levels. This correlation can be at least partially understood as a consequence of the relatively high degree of uniformity in radiation-levels observed within each area. Under such fortunate conditions, the method of using a few hundred field measurements to infer the total radiation profile has yielded apparently realistic values for population exposure, for which the Harvard dosimeter data provide strong qualitative support. Spiers *et al.*, in their discussion of the extensive population investigation in Scotland, have already indicated some of the difficulties involved in obtaining and interpreting data of this type. But it can be concluded from the work recorded here that

the *in situ* approach is capable of yielding useful quantitative results in a reasonably uniform radiation environment, and at the very least can be used as a basis for evaluating more direct—but not necessarily more accurate—methods of estimating mean population exposure-levels.

Another conclusion which is suggested by the New England results is that the basic limitation of the pocket ionization-chamber technique in terms of measuring normal human exposure to environmental radiation is now the difficulty in determining mean leakage rates under actual field conditions while being worn and handled. There appears to be no fundamental reason why this difficulty cannot be at least partially overcome by suitably controlled experimentation, and thus the pocket chamber technique can be considered as a potentially practical one for this kind of measurement. It should be remarked that the dosimeters admirably fulfilled their basic purpose in the Harvard investigation, namely, the determination of differences in population exposure-levels between areas.

There are, of course, a number of other possible methods for determining mean population exposure to environmental radiation. For example, photographic film dosimetry techniques have been applied to this general problem area with some success. O'Brien *et al.*¹⁹ described a film-scintillator (sodium iodide) system which Roser and Cullen²⁰ have utilized in the measurement of population exposure in Brazil on a limited scale. The approximately thousand-fold enhancement of the film response produced by the scintillator is almost too great for the high-background areas of Brazil; such a method would almost certainly be feasible in areas of more normal background levels for certain kinds of studies. The basic limitation here is the cost of the dosimeters, which precludes their widespread use. The problem of reciprocity law failure must also be taken into account in the calibration of the dosimeters.

A similar kind of dosimeter has been described by Henson²¹, using photographic film and a plastic scintillator (*N.E.* 102). While less sensitive than the sodium iodide system, it exhibits little energy dependence and good precision (± 10 per cent *S.D.* for two weeks' exposure at normal background). Reciprocity failure was observed but has not proved excessive. The main problem seems to be a strong dependence on temperature in its response, which varies with the dose rate. The error present in any particular reading is not known, so that the use of this dosimeter has not been recommended.

There has also been recent progress in increasing the sensitivity of normal radiographic film by means of post-exposure to visible light and improved development techniques that may render such film useful for environmental radiation studies without the necessity for external enhancement of its response. McLaughlin²² has reported

roach is capable of yielding useful quantitative information in a reasonably uniform radiation environment, at least can be used as a basis for evaluating mean population exposure-levels. It is not necessarily more accurate—methods of measurement which are suggested by the New York technique in terms of measuring mean leakage rates under conditions while being worn and handled.

It is that the basic limitation of the pocket chamber technique is now determining mean leakage rates under conditions while being worn and handled. There is no fundamental reason why this can be at least partially overcome by suitably designed pocket chamber chamber chamber considered as a potentially practical one measurement. It should be remarked that the chamber has admirably fulfilled their basic purpose in the determination, namely, the determination of mean population exposure-levels between areas.

For example, photographic film has been applied to this general purpose with some success. O'Brien *et al.*¹⁹ described a sodium iodide system which was utilized in the measurement of population exposure on a limited scale. The approximate enhancement of the film response in the measurement of population exposure is almost too great for the use of Brazil; such a method would be feasible in areas of more normal population exposure. The basic cost of the dosimeters, which precludes their use. The problem of reciprocity failure must be taken into account in the use of these dosimeters.

A dosimeter has been described by O'Brien *et al.* which consists of a photographic film and a plastic scintillator. It is more sensitive than the sodium iodide system, has little energy dependence and good stability. The *S.D.* for two weeks' exposure at 100 r is 10%. Reciprocity failure was observed at 100 r. The main problem seems to be the effect of temperature in its response, and the error rate. The error present in any measurement is not known, so that the use of this dosimeter is not recommended.

Recent progress in increasing the sensitivity of photographic film by means of post-exposure treatment and improved development techniques has made such film useful for environmental exposure measurement without the necessity for external calibration. McLaughlin²² has reported

a six-fold increase in the response of commercial radiographic film by use of these techniques that permits a determination of a 3-mr. γ -ray exposure with a precision of ± 0.2 mr.

A very promising approach to the problem of determining human exposure to low-level ionizing radiation has evolved out of the recent development of thermoluminescent materials for personnel dosimetry. Commercially available dosimeter systems using lithium fluoride²³ and calcium fluoride²⁴ are claimed to provide measurable responses at the 10-mr. and 5-mr. level of γ -ray exposure, respectively, with approximately ± 20 per cent accuracy (*S.D.*). These limits may eventually be somewhat lowered and the precision improved with refinements in read-out techniques. Cullen²⁵ has recently utilized 156 lithium fluoride dosimeters for a population exposure investigation in a high background area in Brazil, with 50 mg of the material placed in religious medals to be worn for a three-month period. This exposure time provided a total γ -dose of several hundred milliroentgens, well above the minimum now routinely detectable. In general, thermoluminescent dosimeters have the significant advantages of small size and relatively low unit cost, and may prove to be a useful tool for future population investigations. The Health and Safety Laboratory is at present engaged in evaluating the available thermoluminescent dosimeter systems for their applicability to the routine measurement of human exposure to environmental radiation, and field tests along the lines of the New England survey are planned when sufficiently promising dosimeter systems are developed.

These recent advances in direct personnel dosimetry, particularly in the extension of the sensitivity limits to ever lower γ -dose levels, render the detailed examination of human exposure to environmental radiation on a routine basis increasingly feasible, even in the extremely low-level radiation fields that are characteristic of the normal environment. But the reliability and reproducibility of the readings of the various types of dosimeter in terms of absolute dose under the stresses of actual field use remain to be thoroughly explored. The New England survey results seem to indicate the adequacy of *in situ* measurements in establishing a radiation profile over extensive areas, a profile that when sufficiently uncomplicated may be properly interpreted in terms of population exposure to environmental radiation. These results also emphasize some of the problems associated with adequately calibrating the response of personnel dosimeters under field conditions. It appears that the use of highly accurate ionization-chamber and spectrometric techniques for *in situ* measurements will be required in the near future for all population studies of the type described here, if only to provide a standard by which the adequacy of the new techniques for direct human exposure measure-

ments can be determined (for example, ref. 20). Eventually, it is anticipated that the logistically difficult *in situ* approach will be completely superseded by direct measurements of radiation incident on representative individuals in their daily rounds.

We thank our colleague, H. L. Beck, as well as several Health and Safety Laboratory summer students, including J. Grebowski, H. Grotch and I. Hammerman, for their assistance with the outdoor survey. A. Spiegel carried out the indoor measurements. Many helpful discussions have been held with Dr. A. Segall of the Harvard School of Public Health, who co-ordinated the various parts of the New England survey and who kindly supplied the dosimeter results. We also thank J. E. McLaughlin, director, Radiation Physics Division, Health and Safety Laboratory, for his advice and support.

- ¹ Segall, A., *Science*, **140**, 1337 (1963).
- ² Lowder, W. M., Segall, A., and Condon, W. J., in *The Natural Radiation Environment*, edit. by Adams, J. A. S., and Lowder, W. M. (Univ. Chicago Press, 1964).
- ³ Segall, A., and Reed, R., *Arch. Env. Health*, **9**, 494 (1964).
- ⁴ Condon, W. J., Lowder, W. M., and Beck, H. L., *Health and Safety Lab. Rep.* (to be published, 1965).
- ⁵ Billings, M. P., Harvard Univ. (unpublished results).
- ⁶ Spiers, F. W., App. D, in *The Hazards to Man of Nuclear and Allied Radiations; A Second Report to the Medical Research Council* (H.M. Stationery Office, London, 1960).
- ⁷ Spiers, F. W., McHugh, M. J., and Appleby, D. B., in *The Natural Radiation Environment*, edit. by Adams, J. A. S., and Lowder, W. M. (Univ. Chicago Press, 1964).
- ⁸ Halm, E., Herbst, W., and Mastrocola, A., *Sonderdr. aus Beilage B.*, No. 6/1962, *zum Bull. des Eidg. Gesundheitsamtes* (Dec. 22, 1962).
- ⁹ Spiers, F. W., and Overton, T. R., *Phys. Med. Biol.*, **7**, 35 (1962).
- ¹⁰ O'Brien, K., Lowder, W. M., and Solon, L. R., *Rad. Res.*, **9**, 216 (1958).
- ¹¹ Lowder, W. M., Beck, H. L., and Condon, W. J., in *The Natural Radiation Environment*, edit. by Adams, J. A. S., and Lowder, W. M. (Univ. Chicago Press, 1964).
- ¹² Lowder, W. M., Beck, H. L., and Condon, W. J., *Nature*, **202**, 745 (1964).
- ¹³ Beck, H. L., Condon, W. J., and Lowder, W. M., *Health and Safety Laboratory Report HASL-150* (1964).
- ¹⁴ Beck, H. L. (to be published, 1965).
- ¹⁵ Lowder, W. M., Beck, H. L., and Condon, W. J. (to be published, 1965).
- ¹⁶ Roesch, W. C., McCall, R. C., and Rising, F. L., *Health Phys.*, **1**, 340 (1958).
- ¹⁷ Segall, A., Shapiro, J., and Worcester, J. (to be published).
- ¹⁸ *Rep. U.N. Sci. Comm. Effects of Atomic Radiation* (United Nations, New York, 1962, App. E).
- ¹⁹ O'Brien, K., Solon, L. R., and Lowder, W. M., *Rev. Sci. Instr.*, **29**, 1097 (1958).
- ²⁰ Roser, F. X., and Cullen, T. L., *Science*, **133**, 145 (1962).
- ²¹ Henson, P. W., *Phys. Med. Biol.*, **8**, 423 (1963).
- ²² McLaughlin, W. L., *J. Photogr. Sci.* (to be published, 1965).
- ²³ McCall, R. C., and Fix, R. C., *Health Phys.*, **10**, 602 (1964).
- ²⁴ Blase, E. F., Logerquist, E. F., Palmer, R. C., and Rutland, D. F., *Health Phys.*, **9**, 888 (1963).
- ²⁵ Cullen, T. L. (personal communication, 1964).