

ADMISSION

Central Records
0-1 Hardtack

HEADQUARTERS
TASK GROUP 7.1
Joint Task Force SEVEN
P. O. Box 1663
Los Alamos, New Mexico

TV-4	
Steele	<i>2/21</i>
Jenkins	
Wagon	
Morgan	
McCaughey	
Wasson	

11 March 1958

File No: 0-1, Hardtack I

SUBJECT: Task Group 7.1 Radiological Safety Regulations for Operation HARDTACK

TO: Distribution

1. Transmitted herewith is a copy of the radiological safety regulations that will apply to all Task Group 7.1 personnel during Operation HARDTACK.

2. Your attention is invited to that portion of the regulations concerning film badges. Each individual in the Task Group will be issued a film badge that is to be worn at all times. Dog-tag chains will be provided for a convenient means of wearing the badges. If preferred, individuals may attach the film badge to the security badge rather than using the dog-tag chain. Film badges will be exchanged periodically by all personnel. In addition, upon return from any mission in a contaminated area, badges should be exchanged at the Rad-Safe Center.

3. It is realized that these regulations will not cover all cases that may arise, personnel assigned to Task Unit 6 will be available to advise and assist in handling the problem.

FOR THE COMMANDER:

Gordon L. Jacobs
GORDON L. JACOBS
Commander
Task Unit 6

1 Incl
Rad-Safe Regulations

OL/ppy
DISTRIBUTION:
Total

Hardtack

RECEIVED

MAR 13 1958

LT. 5230

BEST COPY AVAILABLE

du/13

RAD-SAFE REGULATIONS

480

I. RESPONSIBILITIES.

A. The Commander, Joint Task Force SEVEN, is responsible for all radiological safety during Operation HARDACK. The responsibility for general on-site (Eniwetok and Bikini Atolls) radiological safety operations has been delegated to the Commander, Task Group 7.1.

B. The Commander, Task Unit 5, Task Group 7.1, will exercise overall supervision and control for CTG 7.1 on all radiological safety matters.

C. Task Unit Commanders are responsible for the radiological safety of members of their task units. In addition, during operations in contaminated areas, project and party leaders are responsible for radiological safety of the parties and for compliance with these regulations.

II. RADIOLOGICAL SAFETY OPERATIONS.

A. TU-6 rad-safe support services will include:

1. Continuing surveys of the radiological situation at EPG, to include plotting and briefing facilities capable of portraying past and current radiological situations. Reports and maps will be prepared for distribution.
2. Monitoring assistance, training, and advice as requested.
3. Maintenance and issue of monitoring instruments and protective clothing as required.
4. Personnel dosimetry and records service (to include all of JTF SEVEN).
5. Decontamination facilities for personnel, vehicles, and equipment.

B. Exposure Guides and Dosage Control.

1. The total permissible exposures to participating personnel are as follows:
 - a. Gamma: 3.75 röntgens per consecutive 13-week period, with a maximum of 5.0 röntgens for the Operation. Personnel whose previous radiation dose history indicates that their total accumulated dose to 1 January 1958 is in excess of or equal to $5(N-18)$ röntgens, where N is the age on 1 January 1958, will under no circumstances be allowed to exceed the 5.0 R maximum for the Operation.
 - b. Alpha: 10,000 exposure units for any consecutive 13-week period computed by multiplying the average air concentration in the area of exposure in $\mu\text{Ci}/\text{M}^3$ by the hours of exposure. This is to be used in all cases where personnel are not using respiratory protection in an alpha-contaminated area. Natural alpha background is not included in the 10,000 units.
2. The tolerance level for vehicle contamination will be as follows:
 - a. 7 $\mu\text{r}/\text{hr}$ gamma plus beta inside and 7 $\mu\text{r}/\text{hr}$ gamma only outside.

- b. 500 c/a/55cm² fixed alpha. By "fixed" alpha is meant that no change in the alpha contamination level can be observed by swiping a 100cm² area. (55cm² is the area of the normal "Fee Wee" probe.)
- c. 200 c/a/55cm² removable alpha.
3. The tolerance level for personnel contamination will be as follows:
- 7 mr/hr gamma plus beta for outer clothing and shoes, 1 mr/hr gamma on skin or personal clothing. Personal decontamination will be performed when these levels are exceeded.
4. The tolerance level for equipment removed from contaminated areas will be as follows:
- 7 mr/hr gamma only.
 - 500 c/a/55cm² fixed alpha. Decontamination will be performed in the field with portable decontamination equipment prior to return to the main decontamination station if the level exceeds 5,000 c/a/55cm².
5. In the event that reasonable decontamination procedures cannot reduce contamination levels below those levels listed above, CTU-6 will issue appropriate instructions.
6. All personnel will be issued film badges and charge-a-plates on arrival at EPO. The film badge will be worn at all times. In addition, badges will be exchanged after each entry into a contaminated area (exceptions to this will be made in the case of continuing access permits. See below). Lost badges should be reported immediately to TU-6. On return to home station badges will be turned in as part of the EPO check out procedures.
7. TU-6 will process film badges and submit dosage records to Task Unit Commanders on a daily basis. In addition, special reports will be issued on all personnel reaching or exceeding the 2.0 roentgen cumulative dose total. Dosage information may be obtained informally at any time by calling the photo-dosimetry section at the TU-6 Rad-Safe Center.
- C. Entry into Contaminated Areas.
- Radex (radiological exclusion) areas are defined as follows:
 - Full Radex Area: Contamination level of 100 mr/hr or higher.
 - Limited Radex Area: Contamination level of 10 mr/hr but less than 100 mr/hr.
 - Non Radex Area: Contamination level less than 10 mr/hr.
 - Entry into a full radex area will require full protective clothing. In addition, a qualified monitor must accompany any party entering a full radex area. Entry into a limited radex area will require such protective clothing and monitoring support as is deemed necessary by the plotting and briefing section, TU-6.

source strength, and location (by building) is required. This information is desired primarily for the protection of the fire department in the event of fire.

B. No contaminated material will be removed from the EPC without the prior approval of CG 7. All such materials or equipment which are to be removed will be monitored, packaged, labeled and loaded so as to satisfy pertinent regulations concerning shipment of radioactive materials. Such material that will travel by commercial means or unescorted shipment on MAIB must be packaged in accordance with Interstate Commerce Commission regulations. ICB personnel will assist at project and such personnel in obtaining the packaging requirements.

C. Task Unit Commanders are responsible for providing CG 6 with lists of qualified monitors within their Task Units. CG 6 will assist the Task Unit Commanders in qualifying personnel if requested.

WESLEY J. GARDNER